



by Acclaim lighting

1500 Cherokee Parkway, Suite 100, Acworth, GA 30102
Phone: (866) 845-5451 • Fax: (866) 816-6165
E: service@acclaim-lighting.com • www.acclaim-lighting.com

Item No . TP6945-12 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.
Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. Determine the length of chain (18) required to hang the fixture at the desired height. Using quick link (19) attach to the chain loop (20) on top of the fixture (21). Lace fixture wire (16) and ground wire (17) up through every other link of chain (18).
2. Thread the screw collar loop (14) onto the nipple (12) and then thread nipple (12) into the crossbar (9) and secure with the hex nut.
3. Attach crossbar (9) to outlet box (1) using two box screws (11) provided with the outlet box(1). (Note: if the box screws with the outlet box are too short, use the 8-32 x 1" screws provided in the mounting hardware package)
4. Slide the screw collar nut (15), then the canopy (13) onto the end of the chain (18). Fasten the end link of chain to the screw collar loop.
5. Insert the fixture wire (16) and the ground wire (17) up through the nipple (12). Attach the white or ribbed fixture wire to the white supply wire in the outlet box using the twist-on wire connectors provided. Attach the black or smooth fixture wire to the black supply wire in the same manner. Attach the fixture and supply ground wires onto the cross bar using the green ground screw and wire connector.
6. Tuck the wires carefully inside the outlet box. Next raise the canopy (13) to the ceiling and secure in place by screwing the screw collar nut (15) onto the screw collar loop (14).
7. Install a 40 watt maximum medium base bulb (not included) into each socket (24).
8. Raise acrylic diffuser (26) and washer (27) over nipple (25) and secure with ball finial (28).
9. Attach glass discs (22) to fixture (21) and secure with plastic safety helmets as shown.

INSTALLATION IS NOW COMPLETED

